



## DIN-844



krótkie

krótkie

HSS  
Co8Typ  
NR $\lambda=30^\circ$   
 $\gamma=12^\circ$ HSSE  
PMTyp  
HR P $\lambda=30^\circ$   
 $\gamma=10^\circ$ 

AlTiN

$d_1$ k12	$d_2$ h6	$L_2$	$L_1$	Z	INDEX M2-124518		INDEX M4-128517	
6	6	13	57	4	0060	•	0060P	•
7	10	16	66	4	0070	•		
8	10	19	69	4	0080	•	0080P	•
9	10	19	69	4	0090	•		
10	10	22	72	4	0100	•	0100P	•
11	12	22	79	4	0110	•		
12	12	26	83	4	0120	•	0120P	•
13	12	26	83	4	0130	•		
14	12	26	83	4	0140	•	0140P	•
15	12	26	83	4	0150	•		
16	16	32	92	4	0160	•	0160P	•
17	16	32	92	4	0170	•		
18	16	32	92	4	0180	•	0180P	•
20	20	38	104	4	0200	•	0200P	•
22	20	38	104	5	0220	•		
24	25	45	121	5	0240	•		
25	25	45	121	5	0250	•		
26	25	45	121	5	0260	•		
28	25	45	121	5	0280	•		
30	25	45	121	5	0300	•		
32	32	53	133	6	0320	•		