

OPTI




Zastosowanie / Application

| | | |
|---|---------|-------|
| P | 1+6 | 7+14 |
| M | 1+3 | |
| K | 1+3 | 5+6 4 |
| N | 6+9 | |
| S | 6+8 | |
| H | 1, 2, 4 | |

| | | |
|---|---------|-------|
| P | 1+6 | 7+14 |
| M | 1+3 | |
| K | 1+3 | 5+6 4 |
| N | 6+9 | |
| S | 6+8 | |
| H | 1, 2, 4 | |

Wykonanie / Design



HSS
Co8



HSSE
PM

Rodzaj powłoki / Coating

| | |
|---|-------|
| - | AITIN |
|---|-------|

| d ₁ e8 | d ₂ h6 | l ₁ | l ₂ | Z | INDEX | |
|-------------------|-------------------|----------------|----------------|---|----------------|-----------------|
| 17 | 16 | 79 | 19 | 2 | M2-220418-0170 | |
| 18 | 16 | 79 | 19 | 2 | M2-220418-0180 | M4-220417-0180N |
| 19 | 16 | 79 | 19 | 2 | M2-220418-0190 | |
| 20 | 20 | 88 | 22 | 2 | M2-220418-0200 | M4-220417-0200N |
| 22 | 20 | 88 | 22 | 2 | M2-220418-0220 | |
| 24 | 25 | 102 | 26 | 2 | M2-220418-0240 | |
| 25 | 25 | 102 | 26 | 2 | M2-220418-0250 | M4-220417-0250N |
| 25 | 20* | 96 | 26 | 2 | M2-220418-2520 | |
| 26 | 25 | 102 | 26 | 2 | M2-220418-0260 | |
| 28 | 25 | 102 | 26 | 2 | M2-220418-0280 | M4-220417-0280N |
| 28 | 20* | 96 | 26 | 2 | M2-220418-2820 | |
| 30 | 25 | 102 | 26 | 2 | M2-220418-0300 | |
| 32 | 32 | 112 | 32 | 2 | M2-220418-0320 | |
| 36 | 32 | 112 | 32 | 2 | M2-220418-0360 | |
| 40 | 32* | 118 | 38 | 2 | M2-220418-0400 | |

Parametry skrawania str. 101-102

Cutting data page 101-102